

AMENDMENTS TO THE CLAIMS

1. (previously presented) The light housing according to claim 10 comprising at least two attachment arms.
2. (canceled)
3. (previously presented) The light housing according to claim 10, wherein the rear wall has a semi-circular shape.
4. (previously presented) The light housing according to claim 10, wherein the shield further comprises at least one sidewall.
5. (previously presented) The light housing according to claim 4, further comprising two sidewalls, wherein the two sidewalls are curved and the rear wall has a semi-circular shape.
6. (previously presented) The light housing according to claim 5, wherein the curved sidewalls extend from the semi-circular rear wall at substantially the same radius as the semi-circular rear wall so that the two curved sidewalls are contiguous with the semi-circular rear wall and together form a uniform semi-circular shape.
7. (canceled)
8. (previously presented) The light housing according to claim 10, wherein the aperture is arch-shaped.
9. (previously presented) The light housing according to claim 10, wherein the shield further comprises a top that is attached to the top edge and at least partially covers that portion of the shield, which encloses the light source.
10. (currently amended) A light housing for at least partially shielding a light source from a viewer, comprising:
 - a) a light source;
 - b) a shield having a rear wall located between the light source and the viewer, wherein the rear wall has a top edge and a bottom edge, and is formed to partially enclose the light source;
 - c) at least one attachment arm connected to said shield for attaching the shield to a fixed object; and
 - d) an aperture in the rear wall of the shield, wherein the aperture is

contiguous with the bottom edge of the rear wall and wherein a rear portion of the light source is positioned within the aperture.

11. (previously presented) The light housing according to claim 10, wherein the at least one attachment arm is attached to the shield at the bottom edge of the rear wall.
12. (previously presented) The light housing according to claim 10, wherein the at least one attachment arm is injection molded as a unitary construction contiguous with the shield.
13. (previously presented) The light housing according to claim 10, wherein the at least one attachment arm comprises one or more devices selected from the group consisting of glue, screws, clamps, staples, nails, stakes, screws, clamps, tie downs, Velcro®, tape, wire ties, buttons, snaps, weights, hooks, metal rods, or magnetic attachments.
14. (previously presented) The light housing according to claim 10, wherein the attachment arm comprises at least one stake.
15. (previously presented) The light housing according to claim 10, wherein the at least one attachment arm is made from a material selected from the group consisting of steel, stainless steel, aluminum alloys, iron alloys, thermoplastic polymers, thermoset polymers, and cellulosic materials.
16. (previously presented) The light housing according to claim 10, wherein the rear wall is constructed from a material selected from the group consisting of metal, plastic, composite material, and cellulosic material.
17. (previously presented) The light housing according to claim 10, wherein the rear wall comprises a reflective material.
18. (canceled)
19. (currently amended) A light housing for at least partially shielding a light source from a viewer, comprising:
 - a) a light source;
 - b) a shield having a rear wall located between the light source and the viewer, wherein the rear wall has a top edge and a bottom edge, and is formed to partially enclose the light source;

- c) a top that is attached to the top edge and at least partially covers that portion of the shield which encloses the light source;
- d) an arch-shaped aperture in the rear wall of the shield for removably inserting the light source, wherein the arch-shaped aperture is open and contiguous with the bottom edge of the rear wall; and
- e) at least one attachment arm, wherein the attachment arm comprises two round metal stakes, the metal stakes being connected to and extending below the semi-circular rear wall of the shield and function to secure the shield by inserting the stakes into the ground in close proximity to the light source.

20. (canceled)

21. (previously presented) The light housing according to claim 10, wherein the light source comprises an in-ground floodlight.